N 70, Built-in oven, 60 x 60 cm, Stainless steel B57CR22N0



COOKING PASSION SINCE 1877



A⁺









Optional accessories

Z11AB15A0 : Baking tray, non-stick ceramic coated , Z11AU15A0 : Universal pan, non-stick ceramic coated , Z11CR10X0 : Baking and roasting grid (standard) , Z11SZ00X0 : SeamlessCombination mounting kit , Z11TC10X0 : ComfortFlex Rail (1 level) , Z11TC16X0 : ComfortFlex Rail (1 level) and racks , Z12CB10A0 : Baking tray, anthracite enamelled , Z12CL10A0 : Lid for professional pan, enamelled anth , Z12CN10A0 : Professional pan, anthracite enamelled , Z12CU10A0 : Multipurpose pan, anthracite enamelled , Z12TF16X0 : 1 level telescopic rails, full ext,pyro , Z12TF36X0 : 3 level telescopic rails, full ext,pyro , Z13CV05S0 : Cover Strip , Z1913X0 : Baking Stone

Built-in oven with Slide&Hide $^{\odot}$ - unrestricted access to the oven interior thanks to the fully retracting oven door with rotating handle

- $\sqrt{\ \, {\rm Slide\&Hide@}}$ the door disappears underneath the oven for unrestricted access and the handle rotates for easy handling
- $\sqrt{\rm Circo\,Therm^{\it @}}$ our smart hot-air solution for simultaneous baking and roasting on up to four levels
- √ Pyrolytic Self-Cleaning with Easy Clean the duo for optimal cleaning; pyrolytic after heavy use and Easy Clean for in between
- $\sqrt{\,}$ ShiftControl fast navigation through menus and simple operation with the TFT display

Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in

Integrated Cleaning system: Pyrolytic+Hydrolytic

Min. required niche size for installation (HxWxD) : 585-595 x 560-568

x 550 mm

Dimensions : 595 x 596 x 548 mm

Dimensions of the packed product (HxWxD) : 675 x 690 x 660 mm

Control Panel Material : Glass Door Material : Glass Net weight : 40.2 kg Usable volume of cavity : 71 l

Heating modes: : , 4D hot air, Bottom heat, Bread Baking Setting, Dough proving, Full width grill, Gentle heating, Half width grill, Hot

Air-Eco, Hot air grilling, Pizza setting, Top/bottom heat

Oven control : electronic Number of interior lights : 1

Length electrical supply cord: 120.0 cm

EAN code: 4242004177746

Number of cavities (2010/30/EC) : 1

Energy efficiency class (2010/30/EC) : A+

Energy consumption per cycle conventional (2010/30/EC) : 0.87

kWh/cycle

Energy consumption per cycle forced air convection (2010/30/EC) :

0.69 kWh/cycle

Energy efficiency index (2010/30/EC): 81.2 %

Connection Rating : 3600 W Fuse protection : 16 A Voltage : 220-240 V

Plug type: Gardy plug w/ earthing

Included accessories: 1 x enamel baking tray, 1 x combination grid, 1

x universal pan





Features

Type of oven / heating system:

- Oven with 12 heating methods: CircoTherm®, Hotair Eco, Conventional heat, Conventional heat ECO, Hot air grilling, Full surface grill, Half width grill, Pizza setting, Bread Baking, Bottom heat, Low temperature cooking, Dough proving
- Temperature range 40 °C 275 °C
- Cavity volume: 71 l

Hook-in racks / rails

- Number of shelf levels: 4 PC
- Telescopic shelf rails as optional accessory

Design:

• Cavity inner surface: enamel

Cleaning:

- Pyrolytic self-cleaning function
- Easy Clean (program)
- Full glass inner door safer touch door

Comfort:

- 2,5"-TFT- color and text display with touch-control buttons
- Electronic clock
- Temperature proposal Actual temperature display Optical temperature control
- Hide®, the fully retracting oven door
- Slide®, the revolving handle
- Rapid heat
- Halogen interior lighting, Independent oven interior light button
- Cooling fan
- Stainless-steel fan

Accessory:

• 1 x universal pan, 1 x combination grid, 1 x enamel baking tray

Environment and Safety:

- Very low door temperature
- Quadruple glass door panel glazed CoolTouch door
- Automatic door lock during pyrolysis
 Individual adjustable child lock Residual heat indicator Start-/Stop button Door contact switch

Technical Information

- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Total connected load electric: 3.6 KW
- Energy efficiency rating (acc. EU Nr. 65/2014): A+(at a range of energy efficiency classes from A+++ to D)
 Energy consumption per cycle in conventional mode:0.87 kWh
 Energy consumption per cycle in fan-forced convection mode:0.69 kWh


Number of cavities: 1 Heat source: electrical Cavity volume:71 I

Dimensions:

- Appliance dimension (HxWxD): 595 mm x 596 mm x 548 mm
- Niche dimension (HxWxD): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- "Please reference the built-in dimensions provided in the installation drawing"
- We recommend you to choose complementary products within N70, in order to assure an optimal design combination of your Built-In appliances.



Dimensioned drawings



If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

min. worktop thickness	
fitted	flush
37 mm	38 mm
47 mm	48 mm
30 mm	38 mm
27 mm	30 mm
	fitted 37 mm 47 mm 30 mm

