

N 50, fully-integrated dishwasher, 60 cm, XXL, Variable hinge for special installation situations
S275ECX12E



The dishwasher with cutlery drawer that's flexible to load and indicates when it's running, fits even for special built-in situations.

- ✓ Flex 2 Baskets – Flexible baskets, three-stage Rack Matic and Flex Cutlery Drawer offer easy loading
- ✓ Gap Illumination – Tells you when a dishwasher cycle is running.
- ✓ Open Dry – Automatic door opening during the drying phase for even better drying results
- ✓ Chef 70°C – The pro programme that vanishes stubborn residues.
- ✓ Favourite – Easily access your favourite settings or programmes.

Features

Technical Data

Energy Efficiency Class (Regulation (EU) 2017/1369) : D

Energy Consumption for 100 cycles Eco Programme : 85 kWh

Maximum number of place settings : 14

The water consumption of the eco programme in liters per cycle : 9.5 l

Programme duration : 4:35 h

Airborne acoustical noise emissions : 42 dB(A) re 1 pW

Airborne acoustical noise emission class : B

Built-in / Free-standing : Built-in

Height of removable worktop : 0 mm

Dimensions of the product (HxWxD) : 865 x 598 x 550 mm

Min. required niche size for installation (HxWxD) : 865-925 x 600 x 550 mm

Depth with open door 90 degree : 1200 mm

Adjustable feet : Yes - all from front

Maximum adjustability feet : 60 mm

Net weight : 44.6 kg

Gross weight : 46.5 kg

Connection Rating : 2400 W

Fuse protection : 10 A

Voltage : 220-240 V

Repair index : 9.0

Length electrical supply cord : 175.0 cm

Plug type : Gardy plug w/ earthing

Length inlet hose : 165 cm

Length outlet hose : 190 cm

EAN code : 4242004254003

Installation typology : Full-integrated

Optional accessories

Z7863X0	Cutlery basket
Z7870X0	Accessories dishwasher



4 242004 254003

N 50, fully-integrated dishwasher, 60 cm, XXL,
Variable hinge for special installation situations
S275ECX12E

Features

- Energy Efficiency Class¹: D
- Energy² / Water³: 85 kWh / 9.5 litres
- Capacity: 14 place settings
- Programme duration⁴: 4:35 (h:min)
- Noise level: 42 dB(A) re 1 pW
- Noise Efficiency Class: B

NEFF - Header 1

- Home Connect enabled via WLAN

NEFF - Header 2

- 6 programmes: Eco 50 °C, Auto 45-65 °C, Chef 70 °C, Classic 60 °C, Glass 40 °C, Favourite (Pre-Rinse)
- Favourite Programme
- 4 special options: Remote Start, Extra Dry, Power Zone, Extra Speed
- Easy Clean Programme
- Silence on Demand (Quiet now) (via app)

NEFF - Header 3

- Open Dry and Heat exchanger
- AquaSensor®
- DosageAssist
- EfficientSilentDrive
- Detergent Automation
- Self-cleaning filter system with 3-fold corrugated filter
- Interior tub material: Stainless Steel

NEFF - Header 4

- Flex 2 basket system with coloured touchpoints
- Flex Cutlery Drawer
- Rack Matic height-adjustable top basket (3 stage)
- Ball bearing low friction wheels on top basket
- Low friction wheels on bottom basket
- Coloured anti-slip protection strips in top basket
- Rack Stopper to prevent derailing of bottom basket
- 6 foldable plate racks in top basket
- 6 foldable plate racks in bottom basket
- 2 cup shelves with soft silicone front part in top basket
- 2 cup shelves in bottom basket
- Glass rack in bottom basket

NEFF - Header 5

- Controls on top edge of door
- Panel legend: Plain text (english)
- Gap Illumination
- Remaining programme time indicator (min)
- Electronic delay timer: 1-24 hours

NEFF - Header 6

- Aqua Stop®: Neff warranty in case of water damage – for the lifetime of the appliance. *
- incl. Vario Hinge
- Glass Care System
- incl. Salt filling funnel
- incl. Steam protection plate
- Product dimensions (HxWxD): 86.5 x 59.8 x 55 cm

¹ Scale of Energy Efficiency Classes from A to G

² Energy consumption in kWh per 100 cycles (in programme Eco 50 °C)

³ Water consumption in litres per cycle (in programme Eco 50 °C)

⁴ Duration of programme Eco 50 °C

* Please find warranty terms under [please insert here the local URL (internet address, e.g. <https://www.neff-home.com> but with the direct page with the warranty terms)

N 50, fully-integrated dishwasher, 60 cm, XXL,
 Variable hinge for special installation situations
 S275ECX12E

Dimensioned drawings

