

Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, White, Total No Frost KGN39VWEQ





The NoFrost bottomfreezer with VitaFresh: Keeps your fresh foods fresh longer.

- VitaFresh: keeps food fresh for longer in climate controlled drawers at near 0°C.
- Perfect Fit: place your fridge right next to walls or in a niche.
- LED lighting: keep your groceries in perfect view.
- Easy Access Shelf: pull-out glass shelf gives you better access to the contents of your fridge.
- 2 Cooling Systems: separately controllable refrigerator and freezer compartments

Energy Efficiency Class (Regulation (EU) 2017/	1369): E
Average annual energy consumption in kilowati	
(kWh/a):	
Sum of volume of frozen compartments:	
Sum of volume of chill compartments:	
Airborne acoustical noise emissions :	
Airborne acoustical noise emission class:	
Built-in / Free-standing:	
Number of compressors:	
Number of independent cooling systems:	
Width of the appliance:	
Height:	
Depth of the product:	
Net weight:	
Door panel options:	Not possible
Door hinge:	Right reversible
Number of Adjustable Shelves in fridge compar	tment: 3
Shelves for Bottles:	Yes
Frost free system:	Fridge and freezer
Interior ventilator:	No
Reversible Door Hinge:	Yes
Length electrical supply cord:	
Noise level:	
Multi-Flow Air Tower:	
Fast cooling switch:	
Fast freezing function:	
Temperature Controlled Drawer:	
·	
Humidity Control Drawer:	
Number of Door Bins - Refrigerator:	
Door bin adjustability - Refrigerator:	
Tilt-out door bins in fridge:	
Gallon wide door bins:	
Number of Gallon storage:	1
Motorized Shelf:	No
Material ofthe shelves:	Safety glass
Door opened indicator freezer:	No
Automatic motor-driven ice-maker:	No
Connection rating:	100 W
Fuse protection:	
Voltage:	
Frequency:	
Storage Period in Event of Power Failure (h):	
Door panel options:	
Noise level:	
ENERGY STAR® certified:	
Plug type:	
Required cutout/niche size for installation (in):	
Dimensions of the packed product:	
Net weight:	
Gross weight:	174.000 lbs







Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, White, Total No Frost KGN39VWEQ

The NoFrost bottomfreezer with VitaFresh: Keeps your fresh foods fresh longer.

Performance and consumption

Design and Styling

- Doors White, side panels white
- vertical handle
- LED with Soft Start in fridge section

Convenience & Safety

- Separate, electronic temperature control, LED indicators
- Two Cooling Systems
- Super Cooling: automatic deactivation
- Optical and acoustic door open warning system
- Visual / acoustic

Fridge Compartment

- Multi Airflow-System
- without
- 5 safety glass shelves (3 height adjustable), of which 4 x
 EasyAccess Shelf, extendable
- Bottle grid
- 1 door shelf large, 3 door shelf small

Freshness System

- 1 VitaFresh drawer with humidity control Fruits and vegetables retain vitamins and stay fresh for longer.
- -, 1 VitaFresh 0°C drawer Fish and meat stay fresh for longer

Freezer Section

- 3 transparent freezer drawers

Dimensions

- Dimensions (H x W x D): 203.0 cm x 60.0 cm x 66.0 cm

Technical Information

- Door right hinged, reversible
- Height adjustable front feet
- Connected load: 100 W
- Nominal voltage: 220 240 V

Accessories

- ice cube tray

Country Specific Options

- Based on the results of the standard 24-hour test. Actual consumption depends on usage/position of the appliance.
- To achieve the declared energy consumption, the attached distanceholders have to be used. As a result, the appliance depth increases by about 3.5 cm. The appliance used without the distance holder is fully functional, but has a slightly higher energy consumption.

Environment and Safety


Installation


General Information

- Vario Zone removable glass shelves for extra space
- Super Freezing: Manual/automatic activiation
- Freezing possible in all freezer compartments



Series 4, free-standing fridge-freezer with freezer at bottom, 203 x 60 cm, White, Total No Frost KGN39VWEQ





Dimension A:

In models with vertical integrated handles, in order to open easily, a minimum distance of 65 mm is needed.

measurements in mm

